



CMF / CRF Details

CMF ID: 1516

Create directional median openings to allow left-turns and u-turns

Description:

Prior Condition: *No Prior Condition(s)*

Category: Access management

Study: [Signalized Intersections: Informational Guide, Rodegerdts et al., 2004](#)

Star Quality Rating:



[\[View score details\]](#)

Crash Modification Factor (CMF)

Value: 0.49

Adjusted Standard Error:

Unadjusted Standard Error:

Crash Reduction Factor (CRF)

Value: 51 (This value indicates a **decrease** in crashes)

Adjusted Standard Error:

Unadjusted Standard Error:

Applicability

Crash Type:	All
Crash Severity:	All
Roadway Types:	Not specified
Number of Lanes:	
Road Division Type:	
Speed Limit:	
Area Type:	
Traffic Volume:	
Time of Day:	

If countermeasure is intersection-based

Intersection Type:	Other
Intersection Geometry:	
Traffic Control:	Uncontrolled
Major Road Traffic Volume:	14319 to 28154
Minor Road Traffic Volume:	

Development Details

Date Range of Data Used:	
Municipality:	
State:	MI
Country:	

Type of Methodology Used:	Non-regression cross-section
Sample Size Used:	51 Sites

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Dec-01-2009
Comments:	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.