



CMF / CRF Details

CMF ID: 420

Install red-light cameras

Description: RLR enforcement cameras

Prior Condition: *No Prior Condition(s)*

Category: Advanced technology and ITS

Study: [A Multi-Jurisdictional Safety Evaluation of Red Light Cameras, Persaud et al., 2005](#)

Star Quality Rating:



Crash Modification Factor (CMF)

Value: 0.75

Adjusted Standard Error: 0.03

Unadjusted Standard Error: 0.03

Crash Reduction Factor (CRF)

Value: 25 (This value indicates a **decrease** in crashes)

Adjusted Standard Error: 3

Unadjusted Standard Error:

3

Applicability

Crash Type:

Angle

Crash Severity:

All

Roadway Types:

Not specified

Number of Lanes:

Road Division Type:

Speed Limit:

Area Type:

Urban

Traffic Volume:

Time of Day:

If countermeasure is intersection-based

Intersection Type:

Roadway/roadway (not interchange related)

Intersection Geometry:

Not specified

Traffic Control:

Signalized

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used:

Municipality:

State:

Country:	
Type of Methodology Used:	Before/after using empirical Bayes or full Bayes
Sample Size Used:	

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Dec-01-2009
Comments:	Countermeasure name has been slightly modified for consistency across Clearinghouse

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.