



## CMF / CRF Details

**CMF ID: 4262**

**Convert signalized intersection to modern roundabout**

**Description:**

**Prior Condition: Signalized intersection**

**Category: Intersection geometry**

**Study:** [Evaluation of Safety Strategies at Signalized Intersections, Srinivasan, et al., 2011](#)

**Star Quality Rating:**



[\[View score details\]](#)

### Crash Modification Factor (CMF)

**Value:** 1.066

**Adjusted Standard Error:**

**Unadjusted Standard Error:** 0.163

### Crash Reduction Factor (CRF)

**Value:** -6.6 (This value indicates an **increase** in crashes)

**Adjusted Standard Error:**

<b>Unadjusted Standard Error:</b>	16.3
-----------------------------------	------

### Applicability

<b>Crash Type:</b>	All
--------------------	-----

<b>Crash Severity:</b>	All
------------------------	-----

<b>Roadway Types:</b>	Not specified
-----------------------	---------------

<b>Number of Lanes:</b>	1 to 2
-------------------------	--------

<b>Road Division Type:</b>	
----------------------------	--

<b>Speed Limit:</b>	
---------------------	--

<b>Area Type:</b>	Urban and suburban
-------------------	--------------------

<b>Traffic Volume:</b>	
------------------------	--

<b>Time of Day:</b>	Not specified
---------------------	---------------

### *If countermeasure is intersection-based*

<b>Intersection Type:</b>	Roadway/roadway (not interchange related)
---------------------------	---

<b>Intersection Geometry:</b>	3-leg
-------------------------------	-------

<b>Traffic Control:</b>	Roundabout
-------------------------	------------

<b>Major Road Traffic Volume:</b>	5322 to 43123 Annual Average Daily Traffic (AADT)
-----------------------------------	---

<b>Minor Road Traffic Volume:</b>	
-----------------------------------	--

### Development Details

<b>Date Range of Data Used:</b>	1999 to 2009
---------------------------------	--------------

<b>Municipality:</b>	
----------------------	--

<b>State:</b>	CO, FL, IN, MD, MI, NY, NC, SC, VT, WA
---------------	--

<b>Country:</b>	USA
<b>Type of Methodology Used:</b>	Before/after using empirical Bayes or full Bayes
<b>Sample Size Used:</b>	Sites
<b>Before Sample Size Used:</b>	6 Sites
<b>After Sample Size Used:</b>	6 Sites

<b>Other Details</b>	
<b>Included in Highway Safety Manual?</b>	No
<b>Date Added to Clearinghouse:</b>	Dec-06-2012
<b>Comments:</b>	Countermeasure name has been slightly modified for consistency across Clearinghouse

---

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

*The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.*