



CMF / CRF Details

CMF ID: 4855

Installation of an actuated advance warning dilemma zone protection system at high-speed signalized intersections

Description: Installation of an actuated advance warning dilemma zone protection system at high-speed signalized intersections. The design algorithm continually monitors an upstream detector as well as traffic at the intersection in order to predict the onset of the yellow signal indication. Flashing beacons are then used to get the driver's attention and also to warn the driver of the impending end of the green indication.

Prior Condition: Untreated signalized intersection

Category: Intersection traffic control

Study: [*Safety Effect of Dilemma-Zone Protection Using Actuated Advance Warning Systems, Appiah et al., 2011*](#)

Star Quality Rating:



[\[View score details\]](#)

Crash Modification Factor (CMF)

Value: 0.887

Adjusted Standard Error:

Unadjusted Standard Error: 0.105

Crash Reduction Factor (CRF)

Value:	11.3 <i>(This value indicates a decrease in crashes)</i>
Adjusted Standard Error:	
Unadjusted Standard Error:	10.5

Applicability

Crash Type:	All
Crash Severity:	A (serious injury),B (minor injury),C (possible injury)
Roadway Types:	Not specified
Number of Lanes:	
Road Division Type:	
Speed Limit:	
Area Type:	Not specified
Traffic Volume:	
Time of Day:	All

If countermeasure is intersection-based

Intersection Type:	Roadway/roadway (not interchange related)
Intersection Geometry:	4-leg
Traffic Control:	Signalized
Major Road Traffic Volume:	2420 to 21477 Annual Average Daily Traffic (AADT)
Minor Road Traffic Volume:	995 to 8948 Annual Average Daily Traffic (AADT)

Development Details

Date Range of Data Used:	1996 to 2008
Municipality:	
State:	NE
Country:	
Type of Methodology Used:	Before/after using empirical Bayes or full Bayes
Sample Size Used:	
Before Sample Size Used:	179
After Sample Size Used:	167

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	May-01-2013
Comments:	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.