



CMF / CRF Details

CMF ID: 5096

Provide a raised median

Description:

Prior Condition: Two-way left-turn lane

Category: Access management

Study: [*Before-and-after safety study of roadways Where new medians have been added, Alluri et al., 2012*](#)

Star Quality Rating:



[\[View score details\]](#)

Crash Modification Factor (CMF)

Value: 0.998

Adjusted Standard Error:

Unadjusted Standard Error: 0.365

Crash Reduction Factor (CRF)

Value: 0.2 (*This value indicates a **decrease** in crashes*)

Adjusted Standard Error:

Unadjusted Standard Error:	36.5
-----------------------------------	------

Applicability

Crash Type:	Nighttime
Crash Severity:	All
Roadway Types:	Principal Arterial Other
Number of Lanes:	4
Road Division Type:	Divided by TWLTL
Speed Limit:	
Area Type:	Urban and suburban
Traffic Volume:	18340 to 50925 <i>Annual Average Daily Traffic (AADT)</i>
Time of Day:	Night

If countermeasure is intersection-based

Intersection Type:	
Intersection Geometry:	
Traffic Control:	
Major Road Traffic Volume:	
Minor Road Traffic Volume:	

Development Details

Date Range of Data Used:	2003 to 2010
Municipality:	
State:	FL

Country:	USA
Type of Methodology Used:	Simple before/after
Sample Size Used:	Crashes
Before Sample Size Used:	15 Crashes
After Sample Size Used:	17 Crashes

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Aug-01-2013
Comments:	Crashes occurring at dusk

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.