



CMF / CRF Details

CMF ID: 5149

Provide a raised median

Description:

Prior Condition: Two-way left-turn lane

Category: Access management

Study: [*Before-and-after safety study of roadways Where new medians have been added, Alluri et al., 2012*](#)

Star Quality Rating:



[\[View score details\]](#)

Crash Modification Factor (CMF)

Value: 0.783

Adjusted Standard Error:

Unadjusted Standard Error: 0.037

Crash Reduction Factor (CRF)

Value: 21.7 (*This value indicates a **decrease** in crashes*)

Adjusted Standard Error:

Unadjusted Standard Error:	3.7
-----------------------------------	-----

Applicability

Crash Type:	All
--------------------	-----

Crash Severity:	0 (property damage only)
------------------------	--------------------------

Roadway Types:	Principal Arterial Other
-----------------------	--------------------------

Number of Lanes:	4 to 6
-------------------------	--------

Road Division Type:	Divided by TWLTL
----------------------------	------------------

Speed Limit:	
---------------------	--

Area Type:	Urban and suburban
-------------------	--------------------

Traffic Volume:	
------------------------	--

Time of Day:	All
---------------------	-----

If countermeasure is intersection-based

Intersection Type:	
---------------------------	--

Intersection Geometry:	
-------------------------------	--

Traffic Control:	
-------------------------	--

Major Road Traffic Volume:	
-----------------------------------	--

Minor Road Traffic Volume:	
-----------------------------------	--

Development Details

Date Range of Data Used:	2003 to 2010
---------------------------------	--------------

Municipality:	
----------------------	--

State:	FL
---------------	----

Country:	USA
Type of Methodology Used:	Simple before/after
Sample Size Used:	Crashes
Before Sample Size Used:	1009 Crashes
After Sample Size Used:	755 Crashes

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Aug-01-2013
Comments:	-On high-speed arterials (speed limit of either 45, 50, or 55 mph)

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.