



CMF / CRF Details

CMF ID: 5292

10-ft to 70-ft conversion (median width)

Description: Convert a 10-ft traversable median to a 70-ft traversable median

Prior Condition: Median width = 10ft

Category: Access management

Study: [NCHRP Report 633: Impact of Shoulder Width and Median Width on Safety, Stamatiadis et al., 2009](#)

Star Quality Rating:



[\[View score details\]](#)

Crash Modification Factor (CMF)

Value: 0.57

Adjusted Standard Error:

Unadjusted Standard Error:

Crash Reduction Factor (CRF)

Value: 43 (This value indicates a **decrease** in crashes)

Adjusted Standard Error:

Unadjusted Standard Error:

Applicability

Crash Type: Multiple vehicle

Crash Severity: All

Roadway Types: All

Number of Lanes:

Road Division Type: Divided by Median

Speed Limit:

Area Type: Not specified

Traffic Volume:

Time of Day:

If countermeasure is intersection-based

Intersection Type:

Intersection Geometry:

Traffic Control:

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used:

Municipality:

State: CA, KY, MN

Country:	
Type of Methodology Used:	Regression cross-section
Sample Size Used:	14897 Mile-years

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Dec-02-2013
Comments:	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.