



## CMF / CRF Details

**CMF ID: 5412**

**convert lane width from 12 ft to 10 ft, with a total shoulder of X ft**

**Description:** The CMF is for a combination of lane width and shoulder width. X is total paved and unpaved shoulder width in ft.

**Prior Condition:** 12 ft travel lane width and 6 ft shoulder width

**Category:** Roadway

**Study:** [Safety Effects of Cross Section Design on Urban and Suburban Roads, Le and Porter, 2012](#)

**Star Quality Rating:**



[\[View score details\]](#)

### Crash Modification Factor (CMF)

**Value:**

$$CMF = 3.705 * e^{-0.0616 * totshld}$$

**Adjusted Standard Error:**

**Unadjusted Standard Error:**

### Crash Reduction Factor (CRF)

**Value:**

$$CRF = 100 * \left( 1 - \left( 3.705 * e^{-0.0616 * totshld} \right) \right)$$

**Adjusted Standard Error:**

**Unadjusted Standard Error:**

### Applicability

**Crash Type:**

All

**Crash Severity:**

K (fatal),A (serious injury),B (minor injury),C (possible injury)

**Roadway Types:**

Not specified

**Number of Lanes:**

**Road Division Type:**

All

**Speed Limit:**

**Area Type:**

Urban and suburban

**Traffic Volume:**

1183 to 47067 *Annual Average Daily Traffic (AADT)*

**Time of Day:**

All

#### *If countermeasure is intersection-based*

**Intersection Type:**

**Intersection Geometry:**

**Traffic Control:**

**Major Road Traffic Volume:**

**Minor Road Traffic Volume:**

### Development Details

|                                  |                          |
|----------------------------------|--------------------------|
| <b>Date Range of Data Used:</b>  | 2007 to 2009             |
| <b>Municipality:</b>             |                          |
| <b>State:</b>                    | IL                       |
| <b>Country:</b>                  | USA                      |
| <b>Type of Methodology Used:</b> | Regression cross-section |
| <b>Sample Size Used:</b>         | 2004                     |

| <b>Other Details</b>                      |  |
|---|--|
| <b>Included in Highway Safety Manual?</b> | No   |
| <b>Date Added to Clearinghouse:</b>       | Jan-09-2014  |
| <b>Comments:</b>                          | The function includes an interaction between lane width and shoulder width |

---

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

*The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.*