



# CMF / CRF Details

**CMF ID: 8215**

**Install cable median barrier (high tension)**

**Description:**

**Prior Condition: No median barrier**

**Category: Roadside**

**Study: [Development of Crash Modification Factors for Installation of High-Tension Cable Median Barrier, , 2016](#)**



<b>Star Quality Rating:</b>	 <a href="#">[View score details]</a>
-----------------------------	--



<b>Value:</b>	0.76
---------------	------

<b>Adjusted Standard Error:</b>	
---------------------------------	--

<b>Unadjusted Standard Error:</b>	0.11
-----------------------------------	------



<b>Value:</b>	24 (This value indicates a <b>decrease</b> in crashes)
---------------	--

<b>Adjusted Standard Error:</b>	
---------------------------------	--

<b>Unadjusted Standard Error:</b>	11
-----------------------------------	----

### Applicability

<b>Crash Type:</b>	Other
<b>Crash Severity:</b>	Fatal,Serious injury
<b>Roadway Types:</b>	Principal Arterial Other Freeways and Expressways
<b>Number of Lanes:</b>	
<b>Road Division Type:</b>	Divided by Median
<b>Speed Limit:</b>	
<b>Area Type:</b>	
<b>Traffic Volume:</b>	1508 to 99850 <i>Annual Average Daily Traffic (AADT)</i>
<b>Time of Day:</b>	All

### *If countermeasure is intersection-based*

<b>Intersection Type:</b>	
<b>Intersection Geometry:</b>	
<b>Traffic Control:</b>	
<b>Major Road Traffic Volume:</b>	
<b>Minor Road Traffic Volume:</b>	

### Development Details

<b>Date Range of Data Used:</b>	2004 to 2013
<b>Municipality:</b>	
<b>State:</b>	MI

<b>Country:</b>	USA
<b>Type of Methodology Used:</b>	Before/after using empirical Bayes or full Bayes
<b>Sample Size Used:</b>	

<b>Other Details</b>	
<b>Included in Highway Safety Manual?</b>	No
<b>Date Added to Clearinghouse:</b>	Jan-17-2017
<b>Comments:</b>	CMF applies to target crashes on segment with median width 51 to 94 feet. Target crashes refer to any crash in which a crash-involved vehicle left the roadway and entered the median, regardless of whether median entry was a primary or secondary event.

---

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

*The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.*