



CMF / CRF Details

CMF ID: 8215

Install cable median barrier (high tension)

Description:

Prior Condition: No median barrier

Category: Roadside

Study: [Development of Crash Modification Factors for Installation of High-Tension Cable Median Barrier, , 2016](#)

Star Quality Rating:



[\[View score details\]](#)

Crash Modification Factor (CMF)

Value: 0.76

Adjusted Standard Error:

Unadjusted Standard Error: 0.11

Crash Reduction Factor (CRF)

Value: 24 (This value indicates a **decrease** in crashes)

Adjusted Standard Error:

Unadjusted Standard Error:

11

Applicability

Crash Type:

Other

Crash Severity:

K (fatal),A (serious injury)

Roadway Types:

Principal Arterial Other Freeways and Expressways

Number of Lanes:

Road Division Type:

Divided by Median

Speed Limit:

Area Type:

Traffic Volume:

1508 to 99850 *Annual Average Daily Traffic (AADT)*

Time of Day:

All

If countermeasure is intersection-based

Intersection Type:

Intersection Geometry:

Traffic Control:

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used:

2004 to 2013

Municipality:

State:

MI

Country:	USA
Type of Methodology Used:	Before/after using empirical Bayes or full Bayes
Sample Size Used:	

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Jan-17-2017
Comments:	CMF applies to target crashes on segment with median width 51 to 94 feet. Target crashes refer to any crash in which a crash-involved vehicle left the roadway and entered the median, regardless of whether median entry was a primary or secondary event.

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.