



CMF / CRF Details

CMF ID: 8439

Install intersection conflict warning systems (ICWS) for two-lane at two-lane intersections

Description:

Prior Condition: No intersection conflict warning systems

Category: Signs

Study: [Multi-State Safety Evaluation of Intersection Conflict Warning Systems \(ICWS\), Himes et al, 2016](#)

Star Quality Rating:



[\[View score details\]](#)

Crash Modification Factor (CMF)

Value: 0.69

Adjusted Standard Error:

Unadjusted Standard Error: 0.05

Crash Reduction Factor (CRF)

Value: 31 (This value indicates a **decrease** in crashes)

Adjusted Standard Error:

Unadjusted Standard Error:	5
-----------------------------------	---

Applicability

Crash Type:	All
Crash Severity:	A (serious injury),B (minor injury),C (possible injury)
Roadway Types:	Not specified
Number of Lanes:	2
Road Division Type:	
Speed Limit:	
Area Type:	Rural
Traffic Volume:	
Time of Day:	Not specified

If countermeasure is intersection-based

Intersection Type:	Roadway/roadway (not interchange related)
Intersection Geometry:	4-leg
Traffic Control:	Stop-controlled
Major Road Traffic Volume:	
Minor Road Traffic Volume:	

Development Details

Date Range of Data Used:	
Municipality:	
State:	NC

Country:	
Type of Methodology Used:	2
Sample Size Used:	

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Jan-17-2017
Comments:	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.