



## CMF / CRF Details

CMF ID: 8865

### Install Red-light indicator lights

**Description:** Red-light indicator lights are mounted on the signal head or on the mast arm. The indicator activates simultaneously with the red interval, allowing an enforcement officer downstream to identify if a vehicle has violated the red interval.

**Prior Condition:** 4-legged signalized intersection without RLIL

**Category:** Advanced technology and ITS

**Study:** [Safety Evaluation of Red-Light Indicator Lights in Florida, Himes et al., 2017](#)

Star Quality Rating:



[\[View score details\]](#)

### Crash Modification Factor (CMF)

**Value:** 0.614

**Adjusted Standard Error:**

**Unadjusted Standard Error:** 0.054

### Crash Reduction Factor (CRF)

**Value:** 38.6 (This value indicates a **decrease** in crashes)

**Adjusted Standard Error:**

**Unadjusted Standard Error:**

### Applicability

**Crash Type:**

Other

**Crash Severity:**

All

**Roadway Types:**

Not specified

**Number of Lanes:**

**Road Division Type:**

**Speed Limit:**

**Area Type:**

Not specified

**Traffic Volume:**

**Time of Day:**

All

#### *If countermeasure is intersection-based*

**Intersection Type:**

Roadway/roadway (not interchange related)

**Intersection Geometry:**

4-leg

**Traffic Control:**

Signalized

**Major Road Traffic Volume:**

5900 to 80500 Annual Average Daily Traffic (AADT)

**Minor Road Traffic Volume:**

845 to 62666 Annual Average Daily Traffic (AADT)

### Development Details

**Date Range of Data Used:**

2003 to 2012

**Municipality:**

<b>State:</b>	FL
<b>Country:</b>	USA
<b>Type of Methodology Used:</b>	Before/after using empirical Bayes or full Bayes
<b>Sample Size Used:</b>	

<b>Other Details</b>	
<b>Included in Highway Safety Manual?</b>	No
<b>Date Added to Clearinghouse:</b>	Nov-17-2017
<b>Comments:</b>	Disobey signal crashes. Disaggregated CMF for 20% or more of total entering volume from minor approaches

---

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

*The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.*