CMF / CRF Details

CMF ID: 10582

Roundabout geometry

Description: Various geometric elements of roundabout

Prior Condition: No Prior Condition(s)

Category: Intersection geometry

Study: Developing crash modification factors for roundabouts using a

cross-sectional method, Al-Marafi et al., 2020

Star Quality Rating:

2 Stars [View score details]

Crash Modification Factor (CMF)

Value:

 $CMF = e^{-0.02(CD-15)}$

Where CD is the diameter of the central island (m)

Adjusted Standard Error:

Unadjusted Standard Error:

Crash Reduction Factor (CRF)		
Value:	(This value indicates an increase in crashes)	
Adjusted Standard Error:		

Applicability	
Crash Type:	All
Crash Severity:	K (fatal),A (serious injury),B (minor injury),C (possible injury)
Roadway Types:	Not specified
Number of Lanes:	
Road Division Type:	
Speed Limit:	
Area Type:	Not specified
Traffic Volume:	
Time of Day:	
If countermeasure is intersection-based	
Intersection Type:	Roadway/roadway (not interchange related)
Intersection Geometry:	No values chosen.
Traffic Control:	Roundabout
Major Road Traffic Volume:	1288 to 16071 Annual Average Daily Traffic (AADT)
Minor Road Traffic Volume:	1200 to 10002 Annual Average Daily Traffic (AADT)

Development Details		
Date Range of Data Used:	2010 to 2015	
Municipality:	Toowoomba City	
State:		

Country:	Australia
Type of Methodology Used:	7
Sample Size Used:	

Other Details		
Included in Highway Safety Manual?	No	
Date Added to Clearinghouse:	Dec-17-2020	
Comments:	CMFunction for diameter of the central island (m)	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.