



CMF / CRF Details

CMF ID: 10886

Convert intersection to restricted crossing U-turn (RCUT) intersection

Description: The RCUT, also referred to as the superstreet intersection or J-turn intersection. The conversion is for either signalized or stop-controlled.

Prior Condition: Conventional Signalized Intersection

Category: Intersection geometry

Study: [Safety Evaluation of Median U-Turn Crossover-Based Intersections, Al-Omari et al., 2020](#)

Star Quality Rating:	
Star Quality Rating:	<input type="text" value="2 Stars"/>

Crash Modification Factor (CMF)	
Value:	0.7511
Adjusted Standard Error:	
Unadjusted Standard Error:	

Crash Reduction Factor (CRF)	
Value:	24.89 (This value indicates a decrease in crashes)
Adjusted Standard Error:	
Unadjusted Standard Error:	

Applicability

Crash Type: Rear end

Crash Severity: All

Roadway Types: Not specified

Number of Lanes:

Road Division Type: Divided by Median

Speed Limit:

Area Type: Urban and suburban

Traffic Volume:

Time of Day: All

If countermeasure is intersection-based

Intersection Type: Roadway/roadway (not interchange related)

Intersection Geometry: 4-leg

Traffic Control: Signalized

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used: 2003 to 2015

Municipality:

State: MI, NC, OH

Country:

Type of Methodology Used: 1

Sample Size Used:	
--------------------------	--

Other Details	
----------------------	--

Included in Highway Safety Manual?	No
---	----

Date Added to Clearinghouse:	Jul-01-2021
-------------------------------------	-------------

Comments:	
------------------	--

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.