



CMF / CRF Details

CMF ID: 1672

Install flashing beacons as advance warning

Description:

Prior Condition: *No Prior Condition(s)*

Category: Intersection traffic control

Study: [Older Drivers at a Crossroads, Morena et al., 2007](#)



Star Quality Rating:	<input type="text" value="✘ Star"/> [View score details]
-----------------------------	--

Crash Modification Factor (CMF)

Value:	0.64
Adjusted Standard Error:	
Unadjusted Standard Error:	0.138

Crash Reduction Factor (CRF)

Value:	36 (This value indicates a decrease in crashes)
Adjusted Standard Error:	
Unadjusted Standard Error:	13.8

Applicability

Crash Type:	Rear end
Crash Severity:	All
Roadway Types:	Not specified
Number of Lanes:	
Road Division Type:	
Speed Limit:	
Area Type:	All
Traffic Volume:	
Time of Day:	All

If countermeasure is intersection-based

Intersection Type:	Roadway/roadway (not interchange related)
Intersection Geometry:	4-leg
Traffic Control:	Signalized
Major Road Traffic Volume:	
Minor Road Traffic Volume:	

Development Details

Date Range of Data Used:	
Municipality:	
State:	MD
Country:	usa
Type of Methodology Used:	3
Sample Size Used:	Crashes

Before Sample Size Used:	92 Crashes
After Sample Size Used:	28 Crashes

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Dec-01-2009
Comments:	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.