



CMF / CRF Details

CMF ID: 1686

Provide overhead lane-use signs

Description:

Prior Condition: *No Prior Condition(s)*

Category: Intersection traffic control

Study: [Signalized Intersections: Informational Guide, Rodegerdts et al., 2004](#)

Star Quality Rating:	
	<u>Cannot Be Rated</u>

Crash Modification Factor (CMF)	
Value:	0.9
Adjusted Standard Error:	
Unadjusted Standard Error:	

Crash Reduction Factor (CRF)	
Value:	10 (This value indicates a decrease in crashes)
Adjusted Standard Error:	
Unadjusted Standard Error:	

Applicability

Crash Type:	Rear end
Crash Severity:	All
Roadway Types:	Not specified
Number of Lanes:	
Road Division Type:	
Speed Limit:	
Area Type:	
Traffic Volume:	
Time of Day:	

If countermeasure is intersection-based

Intersection Type:	
Intersection Geometry:	
Traffic Control:	
Major Road Traffic Volume:	
Minor Road Traffic Volume:	

Development Details	
Date Range of Data Used:	
Municipality:	
State:	
Country:	
Type of Methodology Used:	
Sample Size Used:	

Other Details

Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Dec-01-2009
Comments:	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.