



# CMF / CRF Details

CMF ID: 2012

Convert 12-ft lanes and 6-ft shoulders to 12-ft lanes and 5-ft shoulders

## Description:

**Prior Condition:** 2-lane rural, undivided. Total width = 30 ft; Lane width = 11 ft; Shoulder width = 4 ft

**Category:** Roadway

**Study:** [Safety Effectiveness of Lane and Shoulder Width Combinations on Rural, Two-Lane, Undivided Roads , Gross et al., 2009](#)

Star Quality Rating:

8 Stars

[\[View score details\]](#)

## Crash Modification Factor (CMF)

**Value:** 0.87

**Adjusted Standard Error:**

**Unadjusted Standard Error:** 0.07

## Crash Reduction Factor (CRF)

**Value:** 13 (This value indicates a **decrease** in crashes)

**Adjusted Standard Error:**

**Unadjusted Standard Error:** 7

**Applicability**

<b>Crash Type:</b>	Run off road
<b>Crash Severity:</b>	All
<b>Roadway Types:</b>	Not Specified
<b>Number of Lanes:</b>	2
<b>Road Division Type:</b>	Undivided
<b>Speed Limit:</b>	
<b>Area Type:</b>	All
<b>Traffic Volume:</b>	1000 <i>Annual Average Daily Traffic (AADT)</i>
<b>Time of Day:</b>	All

***If countermeasure is intersection-based***

<b>Intersection Type:</b>	
<b>Intersection Geometry:</b>	
<b>Traffic Control:</b>	
<b>Major Road Traffic Volume:</b>	
<b>Minor Road Traffic Volume:</b>	

**Development Details**

<b>Date Range of Data Used:</b>	1997 to 2001
<b>Municipality:</b>	
<b>State:</b>	PA
<b>Country:</b>	

<b>Type of Methodology Used:</b>	5
<b>Sample Size Used:</b>	702 Sites

<b>Other Details</b>	
<b>Included in Highway Safety Manual?</b>	No
<b>Date Added to Clearinghouse:</b>	Dec-01-2009
<b>Comments:</b>	

---

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

*The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.*