CMF / CRF Details

CMF ID: 2079

Install transit signal priority (TSP) technology (transit-related crashes)

Description:

Prior Condition: signalized intersection

Category: Transit

Study: Analysis of Transit Safety at Signalized Intersections in Toronto, Shalah et

al., 2009

Star Quality Rating: [View score details]

Crash Modification Factor (CMF)		
Value:	1.26	
Adjusted Standard Error:		
Unadjusted Standard Error:	0.146	

Crash Reduction Factor (CRF)		
Value:	-26 (This value indicates an increase in crashes)	
Adjusted Standard Error:		
Unadjusted Standard Error:	14.6	

Applicability	
Crash Type:	All
Crash Severity:	All
Roadway Types:	Not Specified
Number of Lanes:	
Road Division Type:	
Speed Limit:	
Area Type:	Urban
Traffic Volume:	
Time of Day:	All
If countermeasure is intersection-based	
Intersection Type:	Roadway/roadway (not interchange related)
Intersection Geometry:	
Traffic Control:	Signalized
Major Road Traffic Volume:	3556 to 50877 Annual Average Daily Traffic (AADT)
Minor Road Traffic Volume:	

Development Details		
Date Range of Data Used:	1999 to 2003	
Municipality:	City of Toronto, Canada	
State:		
Country:		
Type of Methodology Used:	7	

Sample Size Used:

1655

Other Details		
Included in Highway Safety Manual?	No	
Date Added to Clearinghouse:	Dec-01-2009	
Comments:	For transit-related crashes.	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.