



CMF / CRF Details

CMF ID: 2080

Presence of far-side transit stop location (transit-related crashes)

Description:

Prior Condition: signalized intersection

Category: Transit

Study: [Analysis of Transit Safety at Signalized Intersections in Toronto, Salah et al., 2009](#)

Star Quality Rating:	
4 Stars	[View score details]

Crash Modification Factor (CMF)	
Value:	0.55
Adjusted Standard Error:	
Unadjusted Standard Error:	0.066

Crash Reduction Factor (CRF)	
Value:	45 (This value indicates a decrease in crashes)
Adjusted Standard Error:	
Unadjusted Standard Error:	6.6

Applicability

Crash Type:

All

Crash Severity:

All

Roadway Types:

Not Specified

Number of Lanes:

Road Division Type:

Speed Limit:

Area Type:

Urban

Traffic Volume:

Time of Day:

All

If countermeasure is intersection-based

Intersection Type:

Roadway/roadway (not interchange related)

Intersection Geometry:

Traffic Control:

Signalized

Major Road Traffic Volume:

3556 to 50877 Annual Average Daily Traffic (AADT)

Minor Road Traffic Volume:

Development Details

Date Range of Data Used:

1998 to 2003

Municipality:

City of Toronto, Canada

State:

Country:

Type of Methodology Used:

7

Sample Size Used:	1655
--------------------------	------

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Dec-01-2009
Comments:	For transit-related crashes.

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.