



CMF / CRF Details

CMF ID: 2198

Presence of speed restriction devices (bike crashes)

Description: Includes red light cameras, speed humps, and other related measures.

Prior Condition: *No Prior Condition(s)*

Category: Advanced technology and ITS

Study: [Assessing Critical Factors Associated with Bicycle Collisions at Urban Signalized Intersections, Oh et al., 2008](#)

Star Quality Rating:

8 Stars

[\[View score details\]](#)

Crash Modification Factor (CMF)

Value: 0.28

Adjusted Standard Error:

Unadjusted Standard Error: 0.22

Crash Reduction Factor (CRF)

Value: 71.92 (This value indicates a **decrease** in crashes)

Adjusted Standard Error:

Unadjusted Standard Error: 22.01

Applicability

Crash Type:	Vehicle/bicycle
Crash Severity:	All
Roadway Types:	Not Specified
Number of Lanes:	
Road Division Type:	
Speed Limit:	
Area Type:	
Traffic Volume:	
Time of Day:	All

If countermeasure is intersection-based

Intersection Type:	
Intersection Geometry:	
Traffic Control:	Signalized
Major Road Traffic Volume:	
Minor Road Traffic Volume:	

Development Details

Date Range of Data Used:	2005 to 2005
Municipality:	Incheon, South Korea
State:	
Country:	

Type of Methodology Used:	7
Sample Size Used:	151

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Dec-01-2009
Comments:	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.