



CMF / CRF Details

CMF ID: 2922

Install a pedestrian hybrid beacon (PHB or HAWK)

Description:

Prior Condition: Minor-road stop-controlled intersection

Category: Pedestrians

Study: [Safety Effectiveness of the HAWK Pedestrian Crossing Treatment, Fitzpatrick, K., and Park, E.S., 2010](#)

Star Quality Rating:	
3 Stars	[View score details]

Crash Modification Factor (CMF)	
Value:	0.309
Adjusted Standard Error:	
Unadjusted Standard Error:	0.156

Crash Reduction Factor (CRF)	
Value:	69 (This value indicates a decrease in crashes)
Adjusted Standard Error:	
Unadjusted Standard Error:	15.6

Applicability

Crash Type: Vehicle/pedestrian

Crash Severity: All

Roadway Types: Not Specified

Number of Lanes: 4 to 6

Road Division Type: All

Speed Limit: 30 to 40 mph

Area Type: Urban and suburban

Traffic Volume:

Time of Day: All

If countermeasure is intersection-based

Intersection Type: Roadway/roadway (not interchange related)

Intersection Geometry: 3-leg,4-leg

Traffic Control: Other

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used: 2002 to 2008

Municipality: Tucson

State: AZ

Country:

Type of Methodology Used: 2

Sample Size Used:	
Before Sample Size Used:	63
After Sample Size Used:	55

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Mar-21-2011
Comments:	The authors of this study also experimented with producing additional CMFs from an alternate dataset of crashes (based on a different definition of relation to intersection). Since this did not add new knowledge to this topic, these CMFs were not included in the Clearinghouse. The CMFs reported in the Clearinghouse reflect the final CMFs noted in the report summary and abstract. The number of crashes in the after period were not reported in this study, however, they have been recorded as 300 to give 10 points as a benefit of doubt for one or more of the following: (1) number of miles/sites in the reference/treatment group, (2) number of crashes in the references/treatment group, (3) reporting AADTs for the aggregate dataset but not for the disaggregate dataset used for CMF development.

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.