



CMF / CRF Details

CMF ID: 2942

Replacement of traditional intersection with roundabout with separated cycle path

Description: Installation of a roundabout with a separated cycle path in place of a traditional (signalized or unsignalized) intersection. Study roundabouts were split between priority to bicyclists and no priority to bicyclists in the cycle lanes.

Prior Condition: Traditional signalized or unsignalized intersection

Category: Bicyclists

Study: [*Injury crashes with bicyclists at roundabouts: influence of some location characteristics and the design of cycle facilities, Daniels et al., 2009*](#)

Star Quality Rating:	
<input type="text" value="2 Stars"/>	[View score details]

Crash Modification Factor (CMF)	
Value:	0.83
Adjusted Standard Error:	
Unadjusted Standard Error:	0.171

Crash Reduction Factor (CRF)	
Value:	17 (This value indicates a decrease in crashes)
Adjusted Standard Error:	

Unadjusted Standard Error:	17.1
-----------------------------------	------

Applicability

Crash Type:	Vehicle/bicycle
--------------------	-----------------

Crash Severity:	All
------------------------	-----

Roadway Types:	Not Specified
-----------------------	---------------

Number of Lanes:	
-------------------------	--

Road Division Type:	All
----------------------------	-----

Speed Limit:	
---------------------	--

Area Type:	Urban
-------------------	-------

Traffic Volume:	
------------------------	--

Time of Day:	All
---------------------	-----

If countermeasure is intersection-based

Intersection Type:	Roadway/roadway (not interchange related)
---------------------------	---

Intersection Geometry:	Not specified
-------------------------------	---------------

Traffic Control:	Roundabout
-------------------------	------------

Major Road Traffic Volume:	
-----------------------------------	--

Minor Road Traffic Volume:	
-----------------------------------	--

Development Details

Date Range of Data Used:	1991 to 2001
---------------------------------	--------------

Municipality:	
----------------------	--

State:	
---------------	--

Country:	Belgium
Type of Methodology Used:	2
Sample Size Used:	Sites
Before Sample Size Used:	38 Sites
After Sample Size Used:	38 Sites

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Mar-21-2011
Comments:	The number of crashes in the after period were not reported in this study, however, they have been recorded as 300 to give 10 points as a benefit of doubt for one or more of the following: (1) number of miles/sites in the reference/treatment group, (2) number of crashes in the references/treatment group, (3) reporting AADTs for the aggregate dataset but not for the disaggregate dataset used for CMF development.

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.