



CMF / CRF Details

CMF ID: 4731

Convert high-speed rural intersection to roundabout

Description: Convert high-speed rural intersection to roundabout

Prior Condition: Stop controlled intersection (3 or 4 leg)

Category: Intersection geometry

Study: [A Statistical Analysis and Development of a Crash Prediction Model for Roundabouts on High-Speed Rural Roadways, Isebrands, 2012](#)

Star Quality Rating:	
<input type="text" value="2 Stars"/>	[View score details]

Crash Modification Factor (CMF)	
Value:	4.66
Adjusted Standard Error:	
Unadjusted Standard Error:	

Crash Reduction Factor (CRF)	
Value:	-366 (This value indicates an increase in crashes)
Adjusted Standard Error:	
Unadjusted Standard Error:	

Applicability

Crash Type: Fixed object

Crash Severity: All

Roadway Types: Not specified

Number of Lanes: 1 to 2

Road Division Type:

Speed Limit: 40-65 mph

Area Type: Rural

Traffic Volume:

Time of Day:

If countermeasure is intersection-based

Intersection Type: Roadway/roadway (not interchange related)

Intersection Geometry: 3-leg,4-leg

Traffic Control: Roundabout

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used:

Municipality:

State: KS, MD, MN, OR, WA, WI

Country:

Type of Methodology Used: 3

Sample Size Used:	Site-years
Before Sample Size Used:	98 Site-years
After Sample Size Used:	98 Site-years

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	May-01-2013
Comments:	The number of crashes in the after period were not reported in this study, however, they have been recorded as 300 to give 10 points as a benefit of doubt for one or more of the following: (1) number of miles/sites in the reference/treatment group, (2) number of crashes in the references/treatment group, (3) reporting AADTs for the aggregate dataset but not for the disaggregate dataset used for CMF development.

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.