



CMF / CRF Details

CMF ID: 5227

Conversion of intersection into low-speed roundabout

Description: Conversion of intersection into low-speed roundabout

Prior Condition: The intersection was operating under no control, yield, TWSC, AWSC, or signal control.

Category: Intersection geometry

Study: [Evaluation of Roundabout Safety, Qin et al., 2013](#)

Star Quality Rating:	
<input type="text" value="✘ Star"/>	[View score details]

Crash Modification Factor (CMF)	
Value:	1.099
Adjusted Standard Error:	
Unadjusted Standard Error:	0.118

Crash Reduction Factor (CRF)	
Value:	-9.94 (This value indicates an increase in crashes)
Adjusted Standard Error:	
Unadjusted Standard Error:	11.8

Applicability

Crash Type:	All
Crash Severity:	All
Roadway Types:	Not specified
Number of Lanes:	2,4
Road Division Type:	All
Speed Limit:	
Area Type:	All
Traffic Volume:	
Time of Day:	All

If countermeasure is intersection-based

Intersection Type:	Roadway/roadway (not interchange related)
Intersection Geometry:	3-leg,4-leg
Traffic Control:	Other
Major Road Traffic Volume:	4100 (total entering) to 48100 (total entering) Annual Average Daily Traffic (AADT)
Minor Road Traffic Volume:	

Development Details

Date Range of Data Used:	1994 to 2010
Municipality:	Statewide
State:	WI
Country:	USA
Type of Methodology Used:	2

Sample Size Used:	Crashes
Before Sample Size Used:	164 Crashes
After Sample Size Used:	180 Crashes

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Aug-01-2013
Comments:	- Study included three-year before and after crash data for each site.- In this case, the reported before-crashes represent the "expected crashes" after treatment.- "Traffic Control" includes intersections with yield control, two-way stop-control, all-way stop-control, and signal control.- Reported traffic volume is total entering volume.

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.