



CMF / CRF Details

CMF ID: 5294

Install shoulder rumble strips

Description:

Prior Condition: No Rumble strips present

Category: Shoulder treatments

Study: [Performance Analysis of Centerline and Shoulder Rumble Strips Installed in Combination in Washington State, D. Olson, M. Sujka, and B. Manchas, 2013](#)

Star Quality Rating:	
<input type="text" value="✘ Star"/>	[View score details]

Crash Modification Factor (CMF)	
Value:	1.123
Adjusted Standard Error:	
Unadjusted Standard Error:	0.598

Crash Reduction Factor (CRF)	
Value:	-12.3 (This value indicates an increase in crashes)
Adjusted Standard Error:	
Unadjusted Standard Error:	59.8

Applicability

Crash Type:

Head on,Run off road,Sideswipe

Crash Severity:

All

Roadway Types:

Not specified

Number of Lanes:

2

Road Division Type:

Speed Limit:

Area Type:

Rural

Traffic Volume:

Time of Day:

If countermeasure is intersection-based

Intersection Type:

Intersection Geometry:

Traffic Control:

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used:

2002 to 2010

Municipality:

State:

WA

Country:

Type of Methodology Used:

3

Sample Size Used:	Crashes
Before Sample Size Used:	5 Crashes
After Sample Size Used:	12 Crashes

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Dec-02-2013
Comments:	VMT based study VMT before = 27.03 MVMT VMT After = 57.69 MVMT Crash type is lane departures.

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.