



CMF / CRF Details

CMF ID: 5510

Increase paved outside shoulder width from 10ft to 12ft

Description: Increase paved outside shoulder width from 10ft to 12ft

Prior Condition: 10 ft paved outside shoulder width

Category: Shoulder treatments

Study: [Using multivariate adaptive regression splines \(MARS\) to develop crash modification factors for urban freeway interchange influence areas , Haleem et al., 2013](#)

Star Quality Rating:	
<input type="text" value="4 Stars"/>	[View score details]

Crash Modification Factor (CMF)	
Value:	0.9
Adjusted Standard Error:	
Unadjusted Standard Error:	0.106

Crash Reduction Factor (CRF)	
Value:	10 (This value indicates a decrease in crashes)
Adjusted Standard Error:	
Unadjusted Standard Error:	10.6

Applicability

Crash Type:	All
Crash Severity:	K (fatal),A (serious injury),B (minor injury),C (possible injury)
Roadway Types:	Principal Arterial Other Freeways and Expressways
Number of Lanes:	4 to 6+
Road Division Type:	Divided by Median
Speed Limit:	
Area Type:	Urban
Traffic Volume:	5700 to 309000 <i>Annual Average Daily Traffic (AADT)</i>
Time of Day:	All

If countermeasure is intersection-based

Intersection Type:	
Intersection Geometry:	
Traffic Control:	
Major Road Traffic Volume:	
Minor Road Traffic Volume:	

Development Details

Date Range of Data Used:	2007 to 2010
Municipality:	
State:	FL
Country:	USA

Type of Methodology Used:	7
Sample Size Used:	18525 Crashes

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Apr-30-2014
Comments:	CMF for urban freeway interchange areas

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.