



CMF / CRF Details

CMF ID: 7743

Install shoulder rumble strips

Description:

Prior Condition: Roadways without should rumble strips

Category: Shoulder treatments

Study: [Validation and Application of Highway Safety Manual \(Part D\) in Florida, Abdel-Aty et al., 2014](#)

Star Quality Rating:

3 Stars

[\[View score details\]](#)

Crash Modification Factor (CMF)

Value: 0.778

Adjusted Standard Error:

Unadjusted Standard Error: 0.118

Crash Reduction Factor (CRF)

Value: 22.2 (This value indicates a **decrease** in crashes)

Adjusted Standard Error:

Unadjusted Standard Error: 11.8

Applicability

Crash Type:

All

Crash Severity:

K (fatal),A (serious injury),B (minor injury),C (possible injury)

Roadway Types:

Not specified

Number of Lanes:

2

Road Division Type:

Undivided

Speed Limit:

Area Type:

Rural

Traffic Volume:

Time of Day:

All

If countermeasure is intersection-based

Intersection Type:

Intersection Geometry:

Traffic Control:

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used:

2007 to 2010

Municipality:

State:

FL

Country:

USA

Type of Methodology Used:

2

Sample Size Used:	
Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Mar-08-2016
Comments:	

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.