



CMF / CRF Details

CMF ID: 7809

10-ft to 60-ft conversion (median width)

Description: Convert a 10-ft traversable median to a 60-ft traversable median

Prior Condition: Roadway with a 10 ft median

Category: Access management

Study: [Validation and Application of Highway Safety Manual \(Part D\) in Florida, Abdel-Aty et al., 2014](#)

Star Quality Rating:	
<input type="text" value="8 Stars"/>	[View score details]

Crash Modification Factor (CMF)	
Value:	0.74
Adjusted Standard Error:	
Unadjusted Standard Error:	0.13

Crash Reduction Factor (CRF)	
Value:	26 (This value indicates a decrease in crashes)
Adjusted Standard Error:	
Unadjusted Standard Error:	13

Applicability

Crash Type:

All

Crash Severity:

All

Roadway Types:

Not specified

Number of Lanes:

4

Road Division Type:

Divided by Median

Speed Limit:

Area Type:

Urban

Traffic Volume:

100 to 97000 *Annual Average Daily Traffic (AADT)*

Time of Day:

All

If countermeasure is intersection-based

Intersection Type:

Intersection Geometry:

Traffic Control:

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used:

2010 to 2012

Municipality:

State:

FL

Country:

USA

Type of Methodology Used:

7

Sample Size Used:	
--------------------------	--

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Mar-08-2016
Comments:	CMFs of widening median width from 10ft to 60ft on urban 4-lane roadways with partial or no access control

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.