



CMF / CRF Details

CMF ID: 8979

Install oversized chevron signs

Description: Curve warning treatment with oversized chevron signs

Prior Condition: smaller 12x18in or 24x30in signs

Category: Signs

Study: [Safety Evaluation of Two Curve Warning Treatments: In-Lane Curve Warning Pavement Markings and Oversized Chevron Signs, Lyon et al., 2017](#)

Star Quality Rating:	
<input type="text" value="8 Stars"/>	[View score details]

Crash Modification Factor (CMF)	
Value:	1.061
Adjusted Standard Error:	
Unadjusted Standard Error:	0.217

Crash Reduction Factor (CRF)	
Value:	-6.1 (This value indicates an increase in crashes)
Adjusted Standard Error:	
Unadjusted Standard Error:	21.7

Applicability

Crash Type: Run off road

Crash Severity: All

Roadway Types: Not specified

Number of Lanes:

Road Division Type:

Speed Limit:

Area Type: Not specified

Traffic Volume: 173 to 27235 Annual Average Daily Traffic (AADT)

Time of Day: Not specified

If countermeasure is intersection-based

Intersection Type:

Intersection Geometry:

Traffic Control:

Major Road Traffic Volume:

Minor Road Traffic Volume:

Development Details

Date Range of Data Used:

Municipality:

State: IA, KS, MO

Country: USA

Type of Methodology Used: 2

Sample Size Used:	
--------------------------	--

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Nov-17-2017
Comments:	Small sample size, use with caution

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.