



CMF / CRF Details

CMF ID: 9124

Install enhanced RRFB pedestrian crossing at mid-block crossing location

Description: Mid-block pedestrian crossings enhanced with Rectangular Rapid Flashing Beacon (RRFB)

Prior Condition: Previously unmarked or at a location with prior high-visibility markings. The data set pooled these locations in the estimation of CMFs.

Category: Pedestrians

Study: [Safety Effectiveness of Pedestrian Crossing Enhancements, Monsere et al., 2017](#)

Star Quality Rating:	
<input type="text" value="✗ Star"/>	[View score details]

Crash Modification Factor (CMF)	
Value:	0.64
Adjusted Standard Error:	
Unadjusted Standard Error:	0.26

Crash Reduction Factor (CRF)	
Value:	36 (This value indicates a decrease in crashes)
Adjusted Standard Error:	
Unadjusted Standard Error:	26

Applicability

Crash Type:	Vehicle/pedestrian
Crash Severity:	All
Roadway Types:	All
Number of Lanes:	2 to 5
Road Division Type:	Undivided
Speed Limit:	20 to 45mph
Area Type:	All
Traffic Volume:	
Time of Day:	All

If countermeasure is intersection-based

Intersection Type:	
Intersection Geometry:	
Traffic Control:	
Major Road Traffic Volume:	
Minor Road Traffic Volume:	

Development Details

Date Range of Data Used:	2007 to 2015
Municipality:	
State:	OR
Country:	USA

Type of Methodology Used:	3
Sample Size Used:	

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Jan-17-2018
Comments:	All pedestrian related crashes

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.