## **CMF / CRF Details**

**CMF ID: 9321** 

Conversion of intersection into single-lane roundabout

Description: Conversion of intersection into single-lane roundabout

Prior Condition: signalized, stop-controlled, yield-controlled and non-controlled intersections

**Category: Intersection geometry** 

Study: Safe roundabouts for cyclists, Jensen, S. U., 2017

Star Quality Rating: [View score details]

Crash Modification Factor (CMF)

Value: 1.98

Adjusted Standard Error: 0.293

Crash Reduction Factor (CRF)	
Value:	-98 (This value indicates an <b>increase</b> in crashes)
Adjusted Standard Error:	
Unadjusted Standard Error:	29.3

Applicability		
Crash Type:	Vehicle/bicycle	
Crash Severity:	All	
Roadway Types:	Not specified	
Number of Lanes:		
Road Division Type:	All	
Speed Limit:	40km/h to 130km/h	
Area Type:	Urban	
Traffic Volume:		
Time of Day:	All	
If countermeasure is intersection-based		
Intersection Type:	Roadway/roadway (not interchange related)	
Intersection Geometry:	No values chosen.	
Traffic Control:	Not specified	
Major Road Traffic Volume:		
Minor Road Traffic Volume:		
Development Date!!s		

Development Details	
Date Range of Data Used:	
Municipality:	
State:	
Country:	Denmark
Type of Methodology Used:	1

## **Sample Size Used:**

Other Details	
Included in Highway Safety Manual?	No
Date Added to Clearinghouse:	Jun-17-2018
Comments:	Type of bicycle facility at roundabout: All urban

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.