



# CMF / CRF Details

CMF ID: 9902

Modify signal phasing (implement a leading pedestrian interval)

Description:

Prior Condition: Signal phasing without leading pedestrian interval

Category: Intersection traffic control

Study: [Safety Evaluation of Protected Left-Turn Phasing and Leading Pedestrian Intervals on Pedestrian Safety, Goughnour et al., 2018](#)

Star Quality Rating:

5 Stars

[\[View score details\]](#)

## Crash Modification Factor (CMF)

Value: 0.83

Adjusted Standard Error:

Unadjusted Standard Error: 0.046

## Crash Reduction Factor (CRF)

Value: 17 (This value indicates a **decrease** in crashes)

Adjusted Standard Error:

Unadjusted Standard Error: 4.6

## Applicability

<b>Crash Type:</b>	All
<b>Crash Severity:</b>	K (fatal),A (serious injury),B (minor injury),C (possible injury)
<b>Roadway Types:</b>	All
<b>Number of Lanes:</b>	
<b>Road Division Type:</b>	
<b>Speed Limit:</b>	
<b>Area Type:</b>	Urban and suburban
<b>Traffic Volume:</b>	
<b>Time of Day:</b>	All

### *If countermeasure is intersection-based*

<b>Intersection Type:</b>	Roadway/roadway (not interchange related)
<b>Intersection Geometry:</b>	Not specified
<b>Traffic Control:</b>	Signalized
<b>Major Road Traffic Volume:</b>	6650 to 32363 Annual Average Daily Traffic (AADT)
<b>Minor Road Traffic Volume:</b>	1850 to 25883 Annual Average Daily Traffic (AADT)

## Development Details

<b>Date Range of Data Used:</b>	2005 to 2014
<b>Municipality:</b>	Chicago
<b>State:</b>	IL
<b>Country:</b>	
<b>Type of Methodology Used:</b>	2

<b>Sample Size Used:</b>	
--------------------------	--

<b>Other Details</b>	
<b>Included in Highway Safety Manual?</b>	No
<b>Date Added to Clearinghouse:</b>	Mar-11-2019
<b>Comments:</b>	Crash Type = Total Injury Crashes. This CMF is for sites where LPIs were implemented either at all crossings (across major and minor roads) or only for crossings across the minor road (parallel to the major road).

---

This site is funded by the U.S. Department of Transportation Federal Highway Administration and maintained by the University of North Carolina Highway Safety Research Center

*The information contained in the Crash Modification Factors (CMF) Clearinghouse is disseminated under the sponsorship of the U.S. Department of Transportation in the interest of information exchange. The U.S. Government assumes no liability for the use of the information contained in the CMF Clearinghouse. The information contained in the CMF Clearinghouse does not constitute a standard, specification, or regulation, nor is it a substitute for sound engineering judgment.*